Geotab Device Installation

The telematics device is a small form-factor device. Device installation is often straightforward and can be completed successfully by following these instructions.

Read important related safety information and limitations of use following these installation instructions. Read and follow all instructions and warnings to prevent serious injury and/or vehicle damage.

Preparing For Installation

Before installing your device, ensure no dash warning lights are on in the vehicle while it is running, and all other functions such as headlamps and flashers etc. are working prior to installing the device.

WARNING! Do not attempt to install, reconfigure or remove any product from a vehicle while the vehicle is in motion or otherwise in operation. All installation, configuration or removal must be done only in stationary vehicles which are securely parked. Attempting to service devices while the vehicle is in motion could result in malfunctions or accidents, leading to death or serious personal injury.


WARNING! An unsecure device installation can cause poor electric and/or data connection that can lead to short circuits and fires or cause malfunctions of vehicle controls that can result in serious personal injury or significant damage to your vehicle. Some examples requiring professional installation from an Authorized Installer are:

- The OBD port location is such that the device could protrude or interfere when entering or exiting the vehicle, or could be inadvertently kicked or bumped during vehicle operation.
- The device isn't fully secured and so may be able to vibrate loose or get kicked or knocked.
- An electrical harness or additional wiring is required.
- Vehicle mounting modifications are required to secure the device i.e. removing of panels, or the OBD connector has been deformed/damaged or there is any physical damage visible to the electrical wiring.
- The device does not beep six times and power on when first installed.
- The installer questions their ability to complete a secure installation according to these instructions.Installation in Four Steps


Based on the warnings above, if you determine that a professional installation by an Authorized Installer is not required, the following basic installation steps can be followed.

Installation Steps









Locate the vehicle's engine diagnostic port typically found in the driver's area at or below knee level.

Align the receiver end of the device with the engine diagnostic port and push in place. Please ensure the device is well connected to the diagnostic port. Once connected, the device emits 6 quick beeps.

Ensure there is always a 20cm separation between the driver and the device.

Once the device is connected and receives power, the LEDs on the front of the device start blinking then turn solid once completing the actions below.

Red LED - Device configuration

Green LED — Cellular network connectivity

Blue LED — GPS network connectivity

Note: The device should be in good cellular coverage during installation process.

The device emits two quick beeps every 60 seconds during set-up. Initial startup may take several minutes to complete.

Once all three LEDs turn solid and you hear 10 quick beeps, secure the device using the provided cable tie.

Note: The device starts updating when the green and blue LEDs turn solid.

WARNING! All in-vehicle devices and related cabling must be securely fastened and kept clear of all vehicle controls, including gas and brake pedals. This requires the use of a cable tie when securing the device or any extension harness to the OBD connector, securing both sides of the harness. If you do not use a cable tie, vibration in the vehicle can lead to a loose connection which could indirectly cause the vehicle's engine computer to fail, loss of vehicle control and cause serious injury. Inspect devices and cabling regularly to ensure all devices and cabling continue to be securely attached.

WARNING! If at any point after an in-vehicle device is installed a warning light illuminates on the vehicle dash or the vehicle stalls or has a marked drop in performance, shut off the engine, remove the device, and contact Chargetrip. Continuing to operate a vehicle with these symptoms can cause loss of vehicle control, and serious injury.

Important Safety Information and Limitations of Use

WARNING! Your in-vehicle devices must be kept clear of debris, water and other environmental contaminants. Failure to do so may result in units malfunctioning or short-circuiting, that can lead to a fire hazard and cause loss or serious injury.

NOTICE: Do not attempt to remove the devices from the vehicle in which they are originally installed for installation in another vehicle. Not all vehicles share compatibility, and doing so may result in unexpected interactions with your vehicle, including sudden loss of power or shutdown of the vehicle's engine while in operation or cause your vehicle to operate poorly or erratically and cause serious injury and/or vehicle damage.

NOTICE: This product does not contain any user-serviceable parts. Configuration, servicing, and repairs must only be made by an authorized reseller (contact Chargetrip). Unauthorized servicing of these products will void your product warranty.

The simplified EU declaration of conformity referred to in Article 10(9) shall be provided as follows:

Hereby, Geotab (Address: 2440 Winston Park Drive, Oakville, Ontario L6H 7V2, Canada, Phone number: 1 (877) 436-8221) declares that the radio equipment type 'telematics device' is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available here.



▲ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.





































For more details on compliance information and applicable products, please contact Chargetrip.